SAFETY DATA SHEET



Lucas DOT 3 Brake Fluid

Section 1. Identification

GHS product identifier : Lucas DOT 3 Brake Fluid

Other means of : Not available.

identification

: 10825, 10826 Product number

Identified uses

Brake and Clutch Systems.

Supplier's details : Lucas Oil Products. Inc

> 302 North Sheridan Street Corona, California 92880-2067 Toll Free: (800) 342-2512 Tel: (951) 270-0154

Fax: (951) 270-1902

Website: www.LucasOil.com

telephone Emergency

number (with hours of

operation)

: (951) 493-1149 (951)847-5949 Markn@lucasoil.com

7:00A.M. to 5:00P.M. Monday thru Friday

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture : SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B

GHS label elements

Signal word : Warning

Hazard statements : Causes eye irritation.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention : Wear eye or face protection. Wash hands thoroughly after handling.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Not applicable. Disposal : Not applicable. Hazards not otherwise

classified

: None known.



Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of : Not available.

identification

CAS number/other identifiers

CAS number : Not applicable.

Product code : 10825, 10826

Ingredient name	%	CAS number
Poly(oxy-1,2-ethanediyl), α-methyl-ω-hydroxy-	10 - 30	9004-74-4
2,2' -Oxybisethanol	1 - 5	111-46-6
2-[2-(2-Butoxyethoxy)ethoxy]ethanol	1 - 5	143-22-6
2-(2-Butoxyethoxy)ethanol	0.1 - 1	112-34-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20

minutes. If irritation persists, get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical

attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

tie, beit of waistband

Skin contact : Flush contaminated skin with plenty of water. Get medical attention if symptoms occur.

 $Wash\ clothing\ before\ reuse.\ Clean\ shoes\ thoroughly\ before\ reuse.$

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person.

If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : May be irritating to mouth, throat and stomach.

Over-exposure signs/symptoms



Section 4. First aid measures

: Adverse symptoms may include the following: Eye contact

> irritation watering redness

Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

: No specific treatment. Specific treatments

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising

from the chemical

Hazardous thermal decomposition products : No specific fire or explosion hazard.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide

Special protective actions

for fire-fighters

Special protective equipment for fire-fighters : No special measures are required.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).



Section 6. Accidental release measures

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2,2' -Oxybisethanol 2-(2-Butoxyethoxy)ethanol	AIHA WEEL (United States, 5/2010). TWA: 10 mg/m³ 8 hours. ACGIH TLV (United States, 6/2013). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures



Section 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

<u>Appearance</u>

Physical state : Liquid.

Color : Pale yellow.

Odor : Mild Ether.

Odor threshold : Not available.

pH : 8.6

Melting point : Not available.

Boiling point : >232.22°C (>450°F)

Flash point : Closed cup: 121.11°C (250°F) [Pensky-Martens.]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 0.824

Solubility : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : 310°C (590°F)



Section 9. Physical and chemical properties

Decomposition temperature : Not available.

Viscosity : Kinematic (100°C (212°F)): >=0.02 cm²/s (>=2 cSt)

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Poly(oxy-1,2-ethanediyl), α-methyl-ω- hydroxy-	LD50 Dermal	Rabbit	>20000 mg/kg	-
2,2'-Oxybisethanol	LD50 Oral LD50 Dermal		39800 mg/kg 11890 mg/kg	-
2,2 -Oxybisetrianoi	LD50 Oral		12000 mg/kg	-
2-[2-(2-Butoxyethoxy)ethoxy]ethanol	LD50 Oral	Rat	5300 mg/kg	-
2-(2-Butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Poly(oxy-1,2-ethanediyl), α-methyl-ω-hydroxy-	Skin - Mild irritant	Rabbit	-	500 mg	-
2,2' -Oxybisethanol	Eyes - Mild irritant	Rabbit	-	50 mg	-
	Skin - Mild irritant	Human	-	72 hours 112 mg Intermittent	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
2-[2-(2-Butoxyethoxy)ethoxy]ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	50 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
2-(2-Butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-

Sensitization

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
2,2' -Oxybisethanol	-	-	-	-	-	None.

Specific target organ toxicity (single exposure)



Section 11. Toxicological information

There is no data available. Specific target organ toxicity

(repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.

Information on the likely

: Dermal contact. Eye contact. Inhalation. Ingestion.

routes of exposure

Potential acute health effects

Eye contact : Causes eye irritation.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : May be irritating to mouth, throat and stomach.

Symptoms related to the physical chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation watering redness

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	16071.4 mg/kg
Dermal	270000 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
1 '			96 hours 96 hours

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2,2' -Oxybisethanol	-1.98	100	low
2-[2-(2-Butoxyethoxy)ethoxy]ethanol	0.51	-	low
2-(2-Butoxyethoxy)ethanol	1	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA	
UN number	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	
Transport hazard class(es)	-	-	-	

			Lucas DOT 3 Brake Fluid
Section 14	. Transport i	nformation	
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

AERG: Not applicable

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according

to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602

Class I Substances

: Not listed

: Listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

(Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	(acute) health	Delayed (chronic) health hazard
Poly(oxy-1,2-ethanediyl), α-methyl-ω-hydroxy- 2,2' -Oxybisethanol 2-[2-(2-Butoxyethoxy)ethoxy]ethanol 2-(2-Butoxyethoxy)ethanol		No. No. No. Yes.	No. No. No.	No. No. No.	Yes. Yes. Yes. Yes.	No. No. No.

SARA 313



Lucas DOT 3 Brake Fluid

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	Butoxyethoxy)ethoxy]ethanol	143-22-6	10 - 30 1 - 5 0.1 - 1
Supplier notification	Butoxyethoxy)ethoxy]ethanol	143-22-6	10 - 30 1 - 5 0.1 - 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : None of the components are listed.

New York : None of the components are listed.

New Jersey : The following components are listed: 2-(2-(2-Methoxyethoxy)ethoxy)ethanol; 2-[2-

(2-Butoxyethoxy)ethoxy]ethanol; 2-(2-Butoxyethoxy)ethanol

Pennsylvania : The following components are listed: 2,2' -Oxybisethanol; 2-(2-(2-Methoxyethoxy)ethoxy)

ethanol; 2-[2-(2-Butoxyethoxy)ethoxy]ethanol; 2-(2-Butoxyethoxy)ethanol

California Prop. 65

No products were found.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 1 * Flammability: 1 Physical hazards: 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 1 Flammability: 1 Instability: 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue mm/dd/yyyy : 06/15/2014

Version : 1

Revised Section(s) : Not applicable.

Prepared by : KMK Regulatory Services Inc.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,



Lucas DOT 3 Brake Fluid

Section 16. Other information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

