

## TECHNICAL DATA SHEET



# SEMI-SYNTHETIC SAE 10W-40 ATV/UTV OIL

PRODUCT # 10720

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>32.0</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8654</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.206</b>
<b>Viscosity @ 40°C, cSt</b>	<b>D-445</b>	<b>81</b>
<b>Viscosity @ 100°C, cSt</b>	<b>D-445</b>	<b>14</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>180</b>
<b>Color</b>		<b>Light Brown</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>422</b>

**Lucas Semi-Synthetic SAE 10W-40 High Performance ATV/UTV Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.**

**Lucas Semi-Synthetic SAE 10W-40 High Performance ATV/UTV Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.**

**The exclusive additive package in Lucas Semi-Synthetic SAE 10W-40 High Performance ATV/UTV Oil allows for extended drain intervals.**

**Lucas Semi-Synthetic SAE 10W-40 High Performance ATV/UTV Oil far exceeds all OEM specifications.**

**Formulated to meet ALL ATV's and UTV's that call for a Semi-Synthetic SAE 10W-40 motor oil.**

**Meets or exceeds: API SG/SF/CC/CD • JASO MA • ACEA A3**