

## TECHNICAL DATA SHEET

# INDUSTRIAL GEAR OIL ISO 220

PRODUCT # 10589, 10590

### TEST

### ASTM

### TYPICAL

|                                |               |              |
|--------------------------------|---------------|--------------|
| <b>API Gravity</b>             | <b>D-1298</b> | <b>28.9</b>  |
| <b>Specific Gravity @ 60°F</b> | <b>D-1298</b> | <b>0.882</b> |
| <b>Lb / Gallon</b>             | <b>D-1298</b> | <b>7.34</b>  |
| <b>Viscosity @ 40°C cSt</b>    | <b>D-445</b>  | <b>220</b>   |
| <b>Flash Point, COC °F</b>     | <b>D-92</b>   | <b>490</b>   |
| <b>Color</b>                   | <b>D-1500</b> | <b>3.0</b>   |

**Lucas Industrial Gear Oil ISO 220 is blended with the highest quality base oils and additives to provide extreme pressure protection, resistance to foam and excellent rust, corrosion and oxidation protection. Non-corrosive to brass, bronze, steel and other copper alloys.**

**Lucas Industrial Gear Oil ISO 220 can be used in chain drives, sprockets, plain and anti-friction bearings, slide guides and flexible couplings. It can be used in manual transmissions, gear canes and worm gears on mobile contractor type equipment. Provides excellent shock loading properties. Lucas Industrial Gear Oil is designed to withstand heavy loads.**

**Meets AGMA (American Gear Manufacturers Association) gear specifications. Recommended for use in bevel, spur, herringbone, planetary, worm and industrial hypoid gears.**