

TECHNICAL DATA SHEET



SAE 10W-30

PRODUCT # 10276, 10338, 10340, 10217

API Service SN, ILSAC GF-5

TEST

ASTM

TYPICAL

API Gravity	D-1298	31.6
Specific Gravity @ 60°F	D-1298	.867
Density @ 60°F LBS/US Gal	D-1298	7.21
Viscosity @ 40°C, cSt	D-445	75.0
Viscosity @ 100°C, cSt	D-445	10.9
Viscosity Index	D-2270	148
Color		Light Brown
Flash Point, COC °F	D-92	455
Pour Point, °C	D-97	-36
CCS @ -25°C, CPS	D-5293	4,230
MRV TP-1 @ -30°C, CPS	D-4684	60,000 Max
P, Wt %	ICP	0.08 Max
Z, Wt %	ICP	0.08 Typical

This excellent product provides the consistent viscosity needed for peak performance. Lucas SAE 10W-30 is a formulation of only the finest light base oils plus an exclusive additive package that includes lubricity agents and anti-seize agents that control drag like a zero weight oil and protect like a heavy multi-viscosity oil.

Lucas SAE 10W-30 is the perfect lubricant for extreme low temperatures or extreme high temperatures and blends with synthetic or regular motor oil.

Designed for use in gasoline engines only.

Meets or exceeds all manufacturers specifications for SAE 10W-30 and API SN and ILSAC GF-5. Exceeds ACEA A1-08, B1-08.