

TECHNICAL DATA SHEET



SYNTHETIC SAE 0W-40 MOTORCYCLE OIL

PRODUCT # 10718, 10756, 10758

TEST

ASTM

TYPICAL

API Gravity	D-1298	35.4
Specific Gravity @ 60°F	D-1298	.8478
Density @ 60°F LBS/US Gal	D-1298	7.059
Viscosity @ 40°C, cSt	D-445	70
Viscosity @ 100°C, cSt	D-445	14
Viscosity Index	D-2270	210
Color		Light Brown
Flash Point, COC °F	D-92	370

Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation. This particular formulation is a high performance blend designed for easy cold weather starting. Especially recommended for snow mobile, 4-stroke engines.

Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

The exclusive additive package in Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil allows for extended drain intervals.

Lucas Synthetic SAE 0W-40 High Performance Motorcycle Oil far exceeds all OEM specifications.

Formulated to meet ALL motorcycles that call for a Synthetic SAE 0W-40 motor oil.

Meets or exceeds: API SM, SL, SJ, SH, SG, SF, CC, CD • JASO MA/MA-2 • ACEA A3