

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 5W-30 MOTORCYCLE OIL

PRODUCT # 10706, 10738, 10740

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>33.1</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8597</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.158</b>
<b>Viscosity @ 40°C, cSt</b>	<b>D-445</b>	<b>55</b>
<b>Viscosity @ 100°C, cSt</b>	<b>D-445</b>	<b>11</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>199</b>
<b>Color</b>		<b>Light Brown</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>435</b>

**Lucas Synthetic SAE 5W-30 High Performance Motorcycle Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.**

**Lucas Synthetic SAE 5W-30 High Performance Motorcycle Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.**

**The exclusive additive package in Lucas Synthetic SAE 5W-30 High Performance Motorcycle Oil allows for extended drain intervals.**

**Lucas Synthetic SAE 5W-30 High Performance Motorcycle Oil far exceeds all OEM specifications.**

**Formulated to meet ALL motorcycles that call for a Synthetic SAE 5W-30 motor oil.**

**Meets or exceeds: API SM, SL, SJ, SH, SG, SF, CC, CD • JASO MA/MA-2 • ACEA A3**