

# TECHNICAL DATA SHEET



## SAE 5W-20

PRODUCT # 10516, 10517, 10518

API Service SN, ILSAC GF-5

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>32.2</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.864</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.205</b>
<b>Viscosity @ 40°C</b>	<b>D-445</b>	<b>47.9</b>
<b>Viscosity @ 100°C</b>	<b>D-445</b>	<b>8</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>149</b>
<b>Color</b>		<b>Clear Brown</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>440</b>

**Lucas SAE 5W-20 is a formulation of high quality base stocks and an exclusive high performance additive package. It's the ideal on track/off track lubricant that ensures minimum drag, maximum protection from wear, maximum fuel mileage and easier cold weather starting.**

**Lucas SAE 5W-20 is the perfect lubricant for the high temperatures of turbo charged engines. It blends with other motor oils, synthetic or petroleum. Expect more miles/kilometers between overhauls and lower oil temperatures.**

**Lucas SAE 5W-20 has been used extensively and proven excellent for kart engines. It far outlasts conventional oils.**

**Exceeds American AND European OEM specifications. Exceeds performance levels of API SN, ILSAC GF-5, ACEA A1-08, B1-08.**