

## TECHNICAL DATA SHEET



# SEMI-SYNTHETIC SAE 10W-40

**PRODUCT # 10176, 10218, 10221, 10373**

**API Service SM/SL/SJ/CF**

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>32.1</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8649</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.202</b>
<b>Viscosity @ 40°C cSt</b>	<b>D-445</b>	<b>97</b>
<b>Viscosity @ 100°C cSt</b>	<b>D-445</b>	<b>15.0</b>
<b>VI</b>		<b>163</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>410</b>
<b>Color</b>		<b>Amber</b>
<b>Zinc, Wt. %</b>		<b>.12</b>

**Lucas Semi Synthetic SAE 10W-40 is a blend of high quality base stocks and an exclusive high performance additive package that ensures minimum drag, extended engine life, longer oil life and easy cold weather starting.**

**Designed for use in both gasoline and automotive diesel engines.**

**The exclusive additive package in Lucas Semi Synthetic SAE 10W-40 allows for extended drain periods.**

**Lucas Semi Synthetic SAE 10W-40 is excellent for use in turbo charged engines. The user can expect longer oil life and lower oil temperature.**

**Meets or exceeds all manufacturers specifications for A3/B3/B4 and API SM/SL/SJ/CF. Exceeds VW 502/505/500 and Ford WSS M2 C 917 A.**