

TECHNICAL DATA SHEET



SYNTHETIC SAE 10W-40

EUROPEAN FORMULA

PRODUCT # 10229, 10230, 10222, 10224

TEST

ASTM

TYPICAL

API Gravity	D-1298	33.5
Specific Gravity @ 60°F	D-1298	.858
Density @ 60°F LBS/US Gal	D-1298	7.15
Viscosity @ 40°C cSt	D-445	87.4
Viscosity @ 100°C cSt	D-445	13.8
VI		163
Flash Point, COC °F	D-92	455
Color		Light Brown
CCS @ -25°C, CPS	D-5293	3,346

Lucas Synthetic SAE 10W-40 Motor Oil is a formulation of high quality synthetic base stocks and an exclusive high performance additive package. It's an ideal on track/off track lubricant that ensures minimum drag for maximum fuel mileage, and easy cold weather starting. The user can expect maximum protection from wear even with extended drain intervals.

The exclusive additive package in Lucas Synthetic SAE 10W-40 ensures extra protection and longer oil life in turbo charged engines. The user can expect lower oil temperatures and more miles/kilometers between overhauls.

Designed for use in both gasoline and automotive diesel engines.

Lucas Synthetic SAE 10W-40 Motor Oil meets the requirements of: ACEA A5/B5-12, ACEA C3-12, ACEA C2-12, API SN, MB-Approval 229.31, MB-Approval 229.51, MB-APPROVAL 229.52, Volkswagen VW50200, Volkswagen VW50500, Volkswagen VW50501, BMW Longlife-04, Porsche Jaguar Land Rover ST JLR.03.5004, FORD WSS-M2C948-B, Volvo Car VCC RBS0-2AE, PSA Peugeot Citroën B712290, GM dexos 2.