## TECHNICAL DATA SHEET



## WHITE LITHIUM GREASE (NLGI #2)

**PRODUCT # 10533** 

| TEST                       | ASTM         | TYPICAL          |
|----------------------------|--------------|------------------|
| Appearance                 | Visual       | Buttery          |
| Color                      | Visual       | White            |
| Soap Type                  |              | Lithium 12HSA    |
| Filler                     |              | Titanium Dioxide |
| Penetration @ 77°F, Worked | D-217        | 265-295          |
| Dropping Point, °F         | D-2265       | 345              |
| Base Oil Viscosity         |              |                  |
| cSt @ 40°C                 | D-445        | 227              |
| cSt @ 100°C                | <b>D-445</b> | 15.0             |
|                            |              |                  |

Lucas White Lithium Grease is formulated with the highest quality base oils and additives to provide mild extreme pressure properties. The white creamy appearance differentiates it from other products. The product is packaged in 8 ounce squeeze tubes for ease of application.

Lucas White Lithium Grease is recommended for use in plain and antifriction bearings operating under moderate load conditions. It is recommended for use in automotive chassis, trucks, tractors and contractor equipment. Not recommended for use in wheel bearings. Our product is truly versatile grease with applications in industrial, automotive and household applications including garage door openers, springs, hinges, etc.